

UAPACM



Access Point UniFi 2.4Ghz da 3 dBi Potenza Max 20dBm / 5.5Ghz da 4 dbi. Potenza Max 20dBm. Wi-Fi Standard 802.11 a/b/g/n/ac, Sicurezza WiFi WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES. Interfaccia Network 10/100/1000 Mbps. Assorbimento 8.5W (max). Montaggio a parete o a soffitto. Indoor/Outdoor.

SCHEDA TECNICA

Articolo	UAPACM
Dimensions	353 x 46 x 34.4 mm (13.9 x 1.81 x 1.35")
Weight	152 g (5.36 oz) with Antennas
Networking Interface	(1) 10/100/1000 Ethernet Port
Buttons	Reset
Power Method	24V Passive PoE (Pairs 4, 5+; 7, 8 Return); 802.3af Alternative A (Pairs 1, 2+; 3, 6 Return) (Supported Voltage Range: 44 to 57VDC)
Power Supply	24V, 0.5A Gigabit PoE Adapter*
Power Save	Supported
Maximum Power Consumption	8.5W
Maximum TX Power	
2.4 GHz	20 dBm
5 GHz	20 dBm
Antennas	(2) External Dual-Band Omni Antennas
2.4 GHz	3 dBi
5 GHz	4 dBi
Wi-Fi Standards	802.11 a/b/g/n/ac
Wireless Security	WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
BSSID	Up to 8 per Radio
Mounting	Wall/Pole/Fast-Mount (Kits Included)
Operating Temperature	-30 to 70° C (-22 to 158° F)
Operating Humidity	5 to 95% Noncondensing
Certifications	CE, FCC, IC